

μCache Packages



Promotional Packages

Each promotional package includes an analog sensor with a 30 cm or 2 m cable, a μCache Bluetooth Micro Logger, a protective neoprene case, an extra μCache battery, and an Apogee PVC sensor platform. When paired, these devices become a powerful tool for measurements with research-grade accuracy for a wide array of applications.

μCache Sensor Packages Quick Reference

	Sensor	Wavelengths	DLI	Recommended for LEDs?	Sensor Cable Length
PQ-100X	SQ-100X	370-650 nm	Y	N	30 cm
PQ-110X	SQ-100X	370-650 nm	Y	N	2 m
PQ-500	SQ-500	400-700 nm	Y	Y	30 cm
PQ-510	SQ-500	400-700 nm	Y	Y	2m
PQ-610	SQ-610	380-760 nm	Y	Y	30 cm
PQ-612	SQ-610	380-760 nm	Y	Y	2 m
PQ-640	SQ-640	340-1040 nm	N	Y	30 cm
P2-141	S2-141	400-700, 700-760 nm	Y	Y	30 cm
P2-142	S2-141	400-700, 700-760 nm	Y	Y	2 m
PP-100	SP-110	360-1120 nm	N	—	30 cm
PP-500	SP-510	385-2105 nm	N	—	30 cm
PE-100	SE-100	CIE 1931 luminous efficiency function	N	Y	30 cm
PU-200	SU-200	305 to 390 nm	N	Y	30 cm
PU-300	SU-300	283-323 nm	N	—	30 cm

PQ-500
Full-spectrum Quantum



P2-142
PAR-FAR Sensor



See our website for other available packages

